



# Hand Oscillating Drum Pump

- *Self Priming*
- *Compact*
- *Cast Iron Construction with Buna-N Seal and Bronze Valves*
- *Delivers 6 GPM, .10 of a Gallon Per Stroke*
- *Suction and Discharge Tube Included*

Cast Iron Hand Oscillating pump is a high quality unit designed for the transfer of and dispensing of lubricating oils and other non-corrosive liquids which are compatible with pump component materials. Pumps will have suction lift of 15 ft. Provides accurate measurement of fluids and will provide up to 50 PSI for prelube applications.



| Catalog Number Stock No. | Description/ Type of Pump       | Ship Wt (Lbs) | Driver Type | Port size Suc x Dis (NPT) | Basic Construction | Seal Type & Elastomer/ Faces |
|--------------------------|---------------------------------|---------------|-------------|---------------------------|--------------------|------------------------------|
| H03/4A4-36DK             | 3/4" Hand Oscillating Drum Pump | 13            | Manual      | 3/4 X 3/4                 | Cast Iron          | Buna-N Lipseal               |

## Standard Features

- Cast Iron Construction
- Buna-N Seal, Bronze Valves and Fiber Gasketing
- Maximum Temperature 120° F
- Maximum Pressure 50 PSI
- 6 GPM @ 60 Strokes per Minute
- 3/4" Suction Tube and Discharge Spout
- 2" Bung Adapter
- Ship Wt. 13 lbs.



See price book page 46

The Gorman-Rupp Company reserves the right to discontinue any model or change specifications at any time without incurring any obligation.

CP123/0904